



APPLICATIONS:

- Formulated biodegradable liquid etchant for removing graffiti from all types of paints



WHAT IS IT FOR:

- Graffiti cleaning delicate surfaces, painted, etc ..

ADVANTAGE

- Easy cleaning graffiti
- Highly effective
- No organic solvents
- Toilet
- neutral Ph

HOW IS IT USED:

Application:

It can be applied by spray, wipe, brush or roller

Leave on for 3-6 minutes depending on the surface.

If you are painted watch not to lift the paint. (Apply only 1-2 minutes)

Exercise caution on painted to avoid damaging the support surfaces.

Repeat if traces remain.

Neutralise with water gently spray.

It manufactured in:

- LIQUID

Packaging:

Pulveriser of 0,750 cc
1-5-25 Kgs

performance*:

3-6 m2/kg

* Indicates performance, depending on the porosity of the support

Attention:

Testing under reduced surface before cleaning.

WARNINGS:

Keep out of the reach of children
Do not discharge into the environment

TEMPERATURES:

Storage temperature: 5°C to 30°C
The product should be applied on the surfaces to a temperature between 5°C and 30°C

HELPFUL CLEANING: with solvent.

STORAGE: 12 months in a dry place.

PROFESSIONAL USE ONLY

PRECAUTIONS:

ECODEC-9 is not flammable but combustible.
Do not smoke or eat during use.
Use with caution on painted surfaces.
Wear gloves and goggles.

TECHNICAL CHARACTERISTICS:

Appearance: Green Liquid
Color: Translucent
Smell: Characteristic

Label elements:



It is recommended to use eye protection and skin and wear appropriate clothing and goggles during work. Avoid splashing and splash on clothing or skin, wash immediately with plenty of water or solvent and remove contaminated clothing. Do not apply flame or incandescent objects. Do not eat drink or smoke during use. Keep away from children. Wastewater produced during pickling, must be collected, separating solids. Waste non-toxic paints may be treated as ordinary waste no need to apply any special treatment. Instead of toxic waste and heavy metal content paints, they are considered special waste and must be treated in a recycling and environmental management. Wash water should not reach sewage or water channels.

DISCLAIMERS:

This information and, in particular, the recommendations relating to the application and end use of the product are given in good faith based on current knowledge and experience of PLX COATS products when properly stored, handled and applied in situations normal in life, according to the recommendations of PLX COATS. In practice, the differences in materials, substrates and actual site conditions of application are such that it can not be inferred from the information in this document, or any written recommendations, or any advice offered no guarantee in terms of merchantability or fitness for a particular purpose, or liability arising out of any legal relationship that might exist. The user of the products must conduct tests to check their suitability for the use that he wants to give. PLX COATS reserves the right to change the properties of its products. Property rights of third parties must be respected. All orders are accepted subject to the terms of our current General Conditions of Sale and Delivery. Users should always refer to the most recent issue of Data Sheets local products, copies of which will be supplied on request or you can get on the page "www.plxcoats.com".