



APPLICATIONS:

- Graffiti
- Paintings
- Perfect for woods

WHAT IS IT FOR:

- Powerful Paint & Graffiti Stripper
- Stripper without acids.

HOW TO USE IT

Application:

Use brush or roller for application on porous supports.

Do not use if the support is painted, as the effectiveness of CAPAZ-V could remove the paint.

It can be applied on brick, plaster, natural stone, concrete, plaster, etc.

Apply on the surface to be treated, insisting with the aid of a brush, with circular movements. Let it act for a few minutes on the graffiti, let it act for 10-30 minutes, or until you notice that the graffiti has started to pull off the surface.

Rinse thoroughly at low pressure with water.

SE FABRICA EN:

- GEL

Repeat the operation as often as necessary to completely eliminate shadows or spectra.

PACKAGING

1-5-25 Kgs

Performance*:

2-5 m2/liter

Attention:

Contains Methylene Chloride

* The yield is indicative, depending on the porosity of the support

WARNINGS:

Keep out of the reach of children
Do not dispose of in the environment

TEMPERATURES:

Storage temperature: 5 ° C to 30 ° C
The product should be applied on surfaces at a temperature between 5 ° C and 30 ° C

USEFUL CLEANING: with Water.

STORAGE: 12 months in a dry place.

EXCLUSIVE USE PROFESSIONALS

PRECAUTIONS:

It is NOT flammable.
Do not smoke or eat during use.
Wear gloves and goggles.

TECHNICAL CHARACTERISTICS:

Appearance: Gel
Color: White translucent
Odor: Spicy

Label elements:



It is recommended to wear eye and skin protection, as well as to wear appropriate protective clothing and goggles during work. Avoid splashes and splashes on clothing or skin, wash immediately with plenty of water or solvent and remove stained clothing. Do not apply on flames or incandescent objects. Do not eat or drink while using. Keep away from children. The wastewater produced during pickling must be collected, separating the solids. Residues of non-toxic paints can be treated as banal waste, not requiring any special treatment. On the other hand, the residues of toxic paints and heavy metal content will be considered special waste and should be treated at a recycling and environmental management point. Wash water must not reach the sewer or aquifers.

LEGAL NOTES:

This information, and in particular the recommendations concerning the application and final use of the product, are given in good faith, based on the current knowledge and experience of PLX COATS products when properly stored, handled and applied in situations Normal, within its useful life, according to the recommendations of PLX COATS. In practice, the possible differences in the materials, supports and actual conditions at the place of application are such that no guarantee can be derived from the information in this document, any other written recommendation, or advice offered, no guarantee in terms of merchantability or fitness for a particular purpose, or any obligation beyond any legal relationship that may exist. The user of the products must carry out the tests to verify their suitability according to the use that is wanted to give. PLX COATS reserves the right to change the properties of its products. The property rights of third parties must be respected. All orders are accepted according to the terms of our current General Conditions of Sale and Delivery. Users should be aware of and use the latest and updated version of the Local Product Data Sheets, a copy of which will be sent to whoever requests them, or can also be obtained from the "www.plxcoats.com" page.