

Liquid paint stripper Paint and graffiti on smooth surfaces



APPLICATIONS:

- Liquid stripper
- Removes graffiti spray and marker



WHAT IS IT FOR:

- Liquid paint stripper Paint and Graffiti
- It is used to clean and protected AQUARET walls.

HOW IS IT USED:

Application::

Use a brush or roller for application on porous substrates.

If the support is painted, make tests in order to avoid damaging the surface, because the effectiveness of the product could remove the paint.

It can be applied on brick, plaster, natural stone, concrete, plaster, etc. Apply on the surface to be treated, insisting with the help of a brush, using circular movements. Leave for a few minutes about the graffiti, leave 10-30 min., Or to see that graffiti has begun to boot from the surface.

Rinse thoroughly with water at low pressure. Repeat as necessary until completely eliminate shadows or ghosts.

It manufactured in:

- Líquid

Packaging:

Pulveriser 0,750 cc
1-5-25 Kgs

performance*:

3-6 m2/litro

* Indicates performance, depending on the porosity of the support

Attention:

Testing under reduced surface before cleaning.

WARNINGS:

Keep out of the reach of children
Do not discharge into the environment

TEMPERATURES:

Storage temperature: 5°C to 30°C
The product should be applied on the surfaces to a temperature between 5°C and 30°C

HELPFUL CLEANING: with solvent.

STORAGE: 12 months in a dry place.

PROFESSIONAL USE ONLY

PRECAUTIONS:

It is flammable and corrosive
Do not smoke or eat during use.
Wear gloves and goggles.

TECHNICAL CHARACTERISTICS:

Appearance: Liquid
Colour: black
Odour: Solvent

Label elements:



It is recommended to use eye protection and skin and wear appropriate clothing and goggles during work. Avoid splashing and splash on clothing or skin, wash immediately with plenty of water or solvent and remove contaminated clothing. Do not apply flame or incandescent objects. Do not eat drink or smoke during use. Keep away from children. Wastewater produced during pickling, must be collected, separating solids. Waste non-toxic paints may be treated as ordinary waste no need to apply any special treatment. Instead of toxic waste and heavy metal content paints, they are considered special waste and must be treated in a recycling and environmental management. Wash water should not reach sewage or water channels.

DISCLAIMERS:

This information and, in particular, the recommendations relating to the application and end use of the product are given in good faith based on current knowledge and experience of PLX COATS products when properly stored, handled and applied in situations normal in life, according to the recommendations of PLX COATS. In practice, the differences in materials, substrates and actual site conditions of application are such that it can not be inferred from the information in this document, or any written recommendations, or any advice offered no guarantee in terms of merchantability or fitness for a particular purpose, or liability arising out of any legal relationship that might exist. The user of the products must conduct tests to check their suitability for the use that he wants to give. PLX COATS reserves the right to change the properties of its products. Property rights of third parties must be respected. All orders are accepted subject to the terms of our current General Conditions of Sale and Delivery. Users should always refer to the most recent issue of Data Sheets local products, copies of which will be supplied supplied on request or you can get on the page "www.plxcoats.com".