

Semi-permanent protection against graffiti



APPLICATIONS:

- Facade

SURFACES:

- Stone
- Metal
- Plastic
- Ceramics
- Concrete

DESCRIPTION:

- Semi-permanent protector for Graffiti.
- 4/5 allows cleanings
- It is not corrosive

It manufactured in:

- SATIN

HOW IS IT USED:

Do not dilute: ready to use.

Application:

It can be applied by brush, roller or spray. Clean dust and dirt from the surface to protect. Apply the product to saturate surface and let dry.

Passed 1-2 hours, the support is ready to apply the permanent protection PLX CRISTAL, improving performance and properties. We advise you not to wait more than 3 hours to apply PLX CRISTAL.

Cleaning graffiti once protected:

Apply DECAPARKS spray, rubbing lightly and rinse with water spray to stop the effect of the cleaner

Packaging:

De 1-5-25 Kgs

Performance*:

8-12 m2/kg

Attention:

You can reapply

* Indicates performance, depending on the porosity of the support

WARNINGS:

Keep out of the reach of children
Do not discharge into the environment

TEMPERATURES:

Storage temperature: 5°C to 30°C
The product should be applied on the surfaces to a temperature between 5°C and 30°C

COMPOSITION:

Waterborne Acrylics

TOOLS CLEANING: with water.

STORAGE: 12 months in a dry place.

PROFESSIONAL USE ONLY

PRECAUTIONS:

It is not flammable.
It is not corrosive.
Use standard safety rules for their application.

TECHNICAL CHARACTERISTICS:

Appearance: Liquid
White colour
Smell: Characteristic

Label elements:

It is recommended to use eye protection and skin and wear appropriate clothing and goggles during work. Avoid splashing and splash on clothing or skin, wash immediately with plenty of water or solvent and remove contaminated clothing.

DISCLAIMERS:

This information and, in particular, the recommendations relating to the application and end use of the product are given in good faith based on current knowledge and experience of PLX COATS products when properly stored, handled and applied in situations normal in life, according to the recommendations of PLX COATS. In practice, the differences in materials, substrates and actual site conditions of application are such that it can not be inferred from the information in this document, or any written recommendations, or any advice offered no guarantee in terms of merchantability or fitness for a particular purpose, or liability arising out of any legal relationship that might exist. The user of the products must conduct tests to check their suitability for the use that he wants to give. PLX COATS reserves the right to change the properties of its products. Property rights of third parties must be respected. All orders are accepted subject to the terms of our current General Conditions of Sale and Delivery. Users should always refer to the most recent issue of Data Sheets local products, copies of which will be supplied on request or you can get on the page "www.plxcoats.com".