# **DECAMARBRE** (D-51)

## Graffiti Remover Shadow in paste















### **APPLICATIONS:**

Eliminates shadows and halos resulting Graffitis that may remain after the use of strippers Recommended



### WHAT IS IT FOR:

Remove persistent shadows of spray and marker in all kinds of surfaces Especially indicated for marble surfaces Oxidizing and coloring effect of all kinds of graffiti shadows

### **HOW IS IT USED:**

#### **Application:**

Ready ready for use.

Application:

Apply with a spatula on marble supports, smearing the shadow of the graffiti, and then cover as a dressing with a plastic sandwich.

Leave on for 24-48-72 hours, depending on the age and depth that the graffiti pigment has penetrated to eliminate.

Rinse abundantly with water under pressure, hot if possible. Repeat the operation as many times as necessary until the leftovers or spectra of paint are completely removed.

### It manufactured in:

PASTE

## Packaging:

De 1-5-25 Kgs

performance\*:

3-6 m2/liter

#### Attention:

Testing under reduced surface before cleaning.

#### **WARNINGS:**

Keep out of the reach of children Do not discharge into the environment

## TEMPERATURES:

Storage temperature: 5°C to 30°C The product should be applied on the surfaces to a temperature between 5°C and 30°C

**HELPFUL CLEANING: with solvent.** 

STORAGE: 12 months in a dry place.

**PROFESSIONAL USE ONLY** 

## PRECAUTIONS:

**DECAMARBREis** not flammable. Wear gloves and goggles. Use standard safety rules for their application.

**TECHNICAL CHARACTERISTICS:** 

Appearance: Liquid **Brown color** 

**Smell: Characteristic** 

Label elements:



It is recommended to use eye protection and skin and wear appropriate clothing and goggles during work. Avoid splashing and splash on clothing or skin, wash immediately with plenty of water or solvent and remove contaminated clothing. Do not apply flame or incandescent objects. Do not eat drink or smoke during use. Keep away from children.

#### DISCLAIMERS:

This information and, in particular, the recommendations relating to the application and end use of the product are given in good faith based on current knowledge and experience of PLX COATS products when properly stored, handled and applied in situations normal in life, according to the recommendations of PLX COATS. In practice, the differences in materials, substrates and actual site conditions of application are such that it can not be inferred from the information in this document, or any written recommendations, or any advice offered no guarantee in terms of merchantability or Conditions of application are social that it cannot be interest interest in the interest in th

<sup>\*</sup> Indicates performance, depending on the porosity of the support